

TechGrid TGU 150

TechGrid TGU 150 uniaxial geogrid is manufactured from high tenacity polyester (PET) yarn, knitted into a structural geogrid network and polymer coated to produce a dimensionally stable product. TechGrid geogrid is inert to biological degradation and resistant to naturally encountered chemicals, alkalis and acids.

TechFab utilizes highly advanced knitting and coating technology to produce world class products engineered for demanding soil reinforcement applications. TechGrid TGU 150 is typically utilized in a variety of soil reinforcement applications such as segmental retaining walls, temporary and permanent wire walls, reinforced slopes, subgrade stabilization, embankments over soft soils, landfill expansions and surcharged embankments.

TechGrid is manufactured in state-of-the-art ISO 9001:2015 certified manufacturing facilities subject to stringent quality control processes at all stages of production. TechFab in-house quality control laboratories are accredited by Geosynthetic Accreditation Institute - Laboratory Accreditation Program (GAI-LAP) and National Accreditation Board for Testing and Calibration Laboratories (NABL).

| Tensile Properties | Test Method | Units | Minimum Average Roll Value (MARV) Machine Direction (MD) |
|--|--------------------------|---------------|--|
| Ultimate Tensile Strength | ASTM D6637 (Method B) | lbs/ft (kN/m) | 10278 (150) |
| Tensile Strength at 5% Strain | ASTM D6637 (Method B) | lbs/ft (kN/m) | 3769 (55) |
| | | | Minimum Roll Value (MD) |
| Creep Limited Strength ¹ | ASTM D6692/D5262 | lbs/ft (kN/m) | 7138 (104.2) |
| Long Term Design Strength (LTDS) ² | | lbs/ft (kN/m) | 6180 (90.2) |

| Physical Properties | Units | Roll Size |
|------------------------------|--------------|------------------------|
| Roll Dimensions ³ | ft (m) | 6.23 x 347 (1.9 x 106) |
| (width x length) | 16 (111) | 6.6 x 328 (2 x 100) |
| Roll Area | $yd^2 (m^2)$ | 240 (200) |
| Fatimental Ball Waight | lbs (kg) | 200.6 (91.0) |
| Estimated Roll Weight | | 200.6 (91.0) |

¹75-year design life

To the best of our knowledge this information is accurate. Final determination of the suitability of any information or material is the sole responsibility of user. TechFab USA does not provide design or engineering services and has not performed any such design services to verify TechFab's material compiles with any particular system, project, purpose, installation or specifications.



² Values based on soils with classifications of sand, silt or clay (SW, SP, SP-SM, SM, SC, CL, ML) RF_{cr}=1.44, RF_{ID}=1.05, RF_D=1.10 Adjustable to other soil types.

³ Custom roll sizes available for special order or large project orders.